

# Typical Specifications

**Model:** GN 1000-2000

**Description:** Fan shall be inline mounted, direct driven, centrifugal exhaust fan.

**Certifications:** Fan shall be manufactured by an ISO 9001 certified company. Fan shall be listed by Underwriters Laboratories (UL 705) and UL listed for Canada (cUL 705). Fan shall bear the AMCA Certified Ratings Seal for Air Performance.

**Construction:** The fan housing shall be minimum 20 gauge galvanized steel and acoustically insulated. Blower and motor assembly shall be mounted to a minimum 14 gauge reinforcing channel. Motor shall be resiliently mounted. Unit shall be supplied with integral wiring box. Discharge position shall be field convertible from straight through, inline configuration to right angle configuration by moving interchangeable panels. The outlet duct collar shall include reinforced aluminum dampers with continuous aluminum hinge rods and brass bushings. To accommodate different ceiling thickness, an adjustable prepunched mounting bracket shall be provided. Unit shall be shipped in ISTA Certified Transit Tested Packaging.

**Wheel:** Wheels shall be twin DWDI centrifugal forward curved type, constructed of galvanized steel. Wheel shall be balanced in accordance with AMCA Standard 204-05, Balance Quality and Vibration Levels for Fans.

**Motor:** Motor shall be totally enclosed type with permanently lubricated bearings and built-in thermal overload protection. Motor shall be furnished at the specified voltage and phase.

**Product:** Fan shall be GN 1000 or GN 2000 series as manufactured by Loren Cook Company of Springfield, Missouri.