

Typical Specifications

- Model:** SWD
- Description:** Fan shall be a wall mounted, direct driven, propeller exhaust fan.
- Certifications:** Fan shall be manufactured at an ISO 9001 certified facility. Fan shall be listed by Underwriters Laboratories (UL 705) and UL listed for Canada (cUL 705). Fan shall bear the AMCA certified ratings seal for sound and air performance.
- Construction:** Fan shall be of bolted and welded construction utilizing corrosion resistant fasteners. The motor shall be mounted on a 12 gauge steel wire guard. The wire guard shall be bolted to a minimum 14 gauge wall panel with continuously welded corners and an integral venturi. Unit shall bear an engraved aluminum nameplate. Nameplate shall indicate design CFM and static pressure. Unit shall be shipped in ISTA certified transit tested packaging.
- Coating:** All steel fan components shall be Lorenized™ with an electrostatically applied, baked polyester powder coating. Each component shall be subject to a five stage environmentally friendly wash system, followed by a minimum 2 mil thick baked powder finish. Paint must exceed 1,000 hour salt spray under ASTM B117 test method.
- Propeller:** Propeller shall have aluminum blades riveted to a painted steel hub. The hub shall be securely fastened to the motor shaft utilizing two setscrews. Propeller shall be balanced in accordance with AMCA Standard 204-05, *Balance Quality and Vibration Levels for Fans*.
- Motor:** Motor shall be 115/1/60, open drip proof type with permanently lubricated sealed bearings.
- Product:** Fan shall be model SWD as manufactured by Loren Cook Company of Springfield, Missouri.